

# Driving towards a green future

SOL EVPOWER Series 2022  
Electric Vehicle Chargers



# Driving towards a green future

SOL EVPOWER Series 2022  
Electric Vehicle Chargers





# Building a sustainable future together

Photo by Reed Naliboff





# Solar for everybody

## The future is solar for everybody

At Solplanet, we aim to power your life with our state-of-the-art PV inverters and smart EV chargers. We strive to create the best possible experience for distributors, installers and end users with the latest certified technologies. That's why our products are easy-to-install, reliable and user-friendly.

Solplanet photovoltaic inverters and EV chargers are manufactured in compliance with international high-quality standards for residential, commercial and governmental installations.

### You can depend on Solplanet

Solplanet is a brand of AISWEI, we've been manufacturing inverters since 2007. Our mother brand, also formerly known as SMA's Chinese subsidiary, has successfully been manufacturing high-quality and reliable products for renowned brands like SMA since 2017 and Zegersolar since 2013. Today, AISWEI is an independent research, development and manufacturing company. A recent equity restructuring puts AISWEI on particularly strong financial footing within the industry.

In 2022, we take a new step to boost our way and promote the global e-mobility revolution, launching our versatile Solplanet EV chargers in the market worldwide.

### Solplanet makes things easy

Our products are easy-to-install, reliable and user-friendly. We offer a variety of quality products with long lasting warranty that you can depend on. Visit our website to explore our wide range of products: Single & three phase PV inverters, hybrid PV inverters, connect and monitoring devices and single & three phase AC EV chargers.

[solplanet.net](https://solplanet.net)



# SOL EVPOWER Series



Series:  
SOL7.4EV  
SOL11EV  
SOL22EV



Easy-to-install

- Compact, lightweight and wall mountable
- Easy-to-install with standard tools
- Quick set-up via Wi-Fi and app



Reliable

- TÜV Rheinland EN/IEC 61851-1/22 compliant
- DC leakage current detection
- IP55 protection suitable for outdoor use
- UV resistant housing and cables



User-friendly

- Scheduled EV charging
- Adjustable charging power
- RFID for user authentication
- LED status indicators

# 7.4 kW

		SOL 7.4 EV-O	SOL 7.4 EV-R	SOL 7.4 EV-WR	SOL 7.4 EVS-O	SOL 7.4 EVS-R	SOL 7.4 EVS-WR
Input & Output	Rate voltage	230 VAC					
	Input Frequency	50 Hz / 60 Hz					
	Max Output Power	7.4 kW					
	Max Output Current	32 A					
	Standby Power	2 W					
	Internal RCD	Type A and DC 6mA RCD function					
	Charging Interface	IEC62196-2, Type 2 plug			IEC62196-2, Type 2 socket		
	Cable Length	5 m			-		
User Interface & Control	Network interface	-	-	Wi-Fi	-	-	Wi-Fi
	RFID	-	●	●	-	●	●
	Status Indication	Halo RGB LED					
	LED Display Screen	●					
	APP	-	-	●	-	-	●
	Communication Protocol	-	-	Support OCPP1.6	-	-	Support OCPP1.6
Working Environment	Protection Level	IP55 (Storage), IP54 (Mated with vehicle)					
	Operating Temperature	-30°C to 50°C					
	StorageTemperature	-40°C to 70°C					
	Relative Humidity	5% to 95% Non-condensing					
	Altitude	Up to 2000 m					
	Cooling	Natural Cooling					
Mechanical	Mounting	Wall					
	Product Dimensions (W / H / D)	237 / 343 / 115 mm					
	Product Net Weight	6 kg			3 kg		
Safety	DC Leakage Protection	●					
	Over Current Protection	●					
	Over Voltage Protection	●					
	Under Voltage Protection	●					
	Over Temperature Protection	●					
	Ground Protection	●					
	Lighting Protection	●					
	Surge Protection	●					
	UV Resistance	●					
	Emergency Stop Button	●					
	Regulation	CE, TUV / EN 61851-1 & EN 61851-22					

● Standard features / ○ optional features / - not available  
Version August 2021

11 kW

		SOL 11 EV-O	SOL 11 EV-R	SOL 11 EV-WR	SOL 11 EVS-O	SOL 11 EVS-R	SOL 11 EVS-WR
Input & Output	Rate voltage	400 VAC					
	Input Frequency	50 Hz / 60 Hz					
	Max Output Power	11 kW					
	Max Output Current	16 A					
	Standby Power	2 W					
	Internal RCD	Type A and DC 6mA RCD function					
	Charging Interface	IEC62196-2, Type 2 plug			IEC62196-2, Type 2 plug		
	Cable Length	5 m			-		
User Interface & Control	Network interface	-	-	Wi-Fi	-	-	Wi-Fi
	RFID	-	●	●	-	●	●
	Status Indication	Halo RGB LED					
	LED Display Screen	●					
	APP	-	-	●	-	-	●
	Communication Protocol	-	-	Support OCPP1.6	-	-	Support OCPP1.6
Working Environment	Protection Level	IP55 (Storage), IP54 (Mated with vehicle)					
	Operating Temperature	-30°C to 50°C					
	StorageTemperature	-40°C to 70°C					
	Relative Humidity	5% to 95% Non-condensing					
	Altitude	Up to 2000 m					
	Cooling	Natural Cooling					
Mechanical	Mounting	Wall					
	Product Dimensions (W / H / D)	237 / 343 / 115 mm					
	Product Net Weight	6 kg			3 kg		
Safety	DC Leakage Protection	●					
	Over Current Protection	●					
	Over Voltage Protection	●					
	Under Voltage Protection	●					
	Over Temperature Protection	●					
	Ground Protection	●					
	Lighting Protection	●					
	Surge Protection	●					
	UV Resistance	●					
	Emergency Stop Button	●					
Regulation	CE, TUV / EN 61851-1 & EN 61851-22						

● Standard features / ○ optional features / – not available  
Version August 2021

22 kW

		SOL 22 EV-O	SOL 22 EV-R	SOL 22 EV-WR	SOL 22 EVS-O	SOL 22 EVS-R	SOL 22 EVS-WR
Input & Output	Rate voltage	400 VAC					
	Input Frequency	50 Hz / 60 Hz					
	Max Output Power	22 kW					
	Max Output Current	32 A					
	Standby Power	2 W					
	Internal RCD	Type A and DC 6mA RCD function					
	Charging Interface	IEC62196-2, Type 2 plug			IEC62196-2, Type 2 socket		
	Cable Length	5 m			-		
User Interface & Control	Network interface	-	-	Wi-Fi	-	-	Wi-Fi
	RFID	-	●	●	-	●	●
	Status Indication	Halo RGB LED					
	LED Display Screen	●					
	APP	-	-	●	-	-	●
	Communication Protocol	-	-	Support OCPP1.6	-	-	Support OCPP1.6
Working Environment	Protection Level	IP55 (Storage), IP54 (Mated with vehicle)					
	Operating Temperature	-30°C to 50°C					
	StorageTemperature	-40°C to 70°C					
	Relative Humidity	5% to 95% Non-condensing					
	Altitude	Up to 2000 m					
	Cooling	Natural Cooling					
Mechanical	Mounting	Wall					
	Product Dimensions (W / H / D)	237 / 343 / 115 mm					
	Product Net Weight	6 kg			3 kg		
Safety	DC Leakage Protection	●					
	Over Current Protection	●					
	Over Voltage Protection	●					
	Under Voltage Protection	●					
	Over Temperature Protection	●					
	Ground Protection	●					
	Lighting Protection	●					
	Surge Protection	●					
	UV Resistance	●					
	Emergency Stop Button	●					
Regulation	CE, TUV / EN 61851-1 & EN 61851-22						

● Standard features / ○ optional features / – not available  
Version August 2021




# Solar energy made easy!






We strive to create the best possible experience for distributors, installers and end users. That’s why our products are easy-to-install, reliable and user-friendly.

Explore our product catalogue



We offer a variety of high-quality products designed to cover your needs, no matter the size of your installation:

	Easy-to-install	<ul style="list-style-type: none"><li>• Quick &amp; easy-to-install with basic standard tools.</li><li>• Quick Wi-Fi set up with app</li><li>• Compact designs with wall mount fixture</li></ul>
	Reliable	<ul style="list-style-type: none"><li>• International quality standards</li><li>• Integrated large range DC/AC switch</li><li>• IP65 waterproof for outdoor use</li></ul>
	User-friendly	<ul style="list-style-type: none"><li>• Smart monitoring with user-friendly app</li><li>• Discrete design that fits anywhere</li><li>• Quiet performance with low dB levels</li></ul>

	Single phase string inverters		
	Three phase string inverters		AC EV Chargers
	Hybrid inverters		Connect & monitor devices

# www.solplanet.net



Photo by Johannes Plenio

## Contact your local office:

### INTERNATIONAL

info@solplanet.net  
sales@solplanet.net  
service@solplanet.net

### AUSTRALIA

Sales: +61 390 988 674  
sales.au@solplanet.net  
Service: +61 390 988 674  
service.au@solplanet.net

### THE NETHERLANDS

Sales: +31 202 402 557  
sales.nl@solplanet.net  
Service: +31 20 800 4844  
service.eu@solplanet.net

### POLAND

Sales: +48 600 721 791  
sales.pl@solplanet.net  
Service: +48 134 926 109  
service.pl@solplanet.net

### TURKEY

Sales: +90 5546311089  
sales.tr@solplanet.net  
service.eu@solplanet.net

### AIWEI GREATER CHINA

Sales: +86 512 6937 2978  
sales.china@aiswei-tech.com  
Service: +86 400 801 9996  
service.china@aiswei-tech.com